

Fixture X Rev. 2.0- LA Metro tunnel lighting

Go Green Tunnel Fixture X; Rev. 2.0 (4' EMX Holophane 4000K)



Features:

- 4,833 lumens/ 4,000 kelvin/ 80 CRI/ 277 volts/ 38 watts
- LLF calc in emergency mode @ 50% operational maintains 1.3fc @ L70*
- Weight 19.4 lbs/ 47.7" long x 4.6" high (with std bkt) x 5.1" wide
- Dual solid-state drivers with individual in-line fuse connectors
- Littlefuse 300volt time-delay #LMF005 fuses with #LHR000 fuse holders (or equivalent)
- Dual LED light modules with individual quick connectors
- Aluminum housing with polyester powder coated corrosion resistant White paint
- 18-8 stainless steel rear brackets and enclosure screws
- Frosted V2, .125" thick polycarbonate external frosted lens with internal Wide Optic
- Blue Frosted lens option available as Part #EMX-BFL
- CSA US & Canadian certified to C22.2#250.0-18, 13-17, UL 1598 & UL 8750*
- Wet certified to IP69K (Ingress Protection). Highest standard for dust& water intrusion
Marine certified to 5000hour salt/fog test, 1,500 psi water test & up to 70 degrees C
- NEMA 4X rated/ 10kV surge rated per ANSI C82.77-5-2015
- Radiated Emissions comply with FCC Title 47, Part 15, Subpart B*
- Manufactured in the United States
- Warranty: 10 years against failure or lumen reduction below 70% of initial luminance

*Please see attached lumen analysis, CSA certification & radiated emissions test.

Mounting Options: Each fixture is provided with a pair of standard mount or rigid mount brackets for installation to wall mount unistrut or other bracket configuration. Alternate brackets for angle or pole mounting options are shown below.

Standard Mount




(ceiling, suspended)

Rigid mount bracket (RMBK)



(ceiling, wall, suspended)

Angled rigid mount bracket (RMBA)



(angled)

Rigid mount U-bolt (RMBU)



(pole)

